

EMBLEM EASY Tape Textile

EMBLEM EASY Tape Textile

| | |
|---|--|
| Material: | double sided adhesive tape |
| Carrier: | scrim of PES/PVA |
| Liner: | both sided silico-nised liner, 90 g/m ² |
| Colour of glue: | transparent |
| Weight of glue: | 230 g/m ² |
| Total thickness: | 240 µm |
| Adhesive: | modified polyacrylate, permanent |
| Peel adhesion on steel: after 1h (acc. AFERA 5001) | min. 30 N/25 mm |
| Appl. temperature: | > +10°C |
| Temperature resistance: | -40°C to +100°C |
| Width of roll: | 25 mm |
| Length of roll: | 25 m |
| Storage: | cool and dry, no direct sun exposure |

There is a possibility of lateral leakage of glue caused by storing over recommended storage temperature. Thereby the adhesive property are not impaired. In order to avoid a sticking of the individual windings together, the rolls should be flat stored on a silico-nised paper.

Mechanical effects must be avoided, since this can involve to sticking together of the winding.

Description:

EMBLEM EASY Tape Textile is a very strongly sticking, double-sided adhesive tape with high tack. The adhesive based on a modified polyacrylate. The adhesive indicates a high humidity and climatic stability when in use.

The PES/PVA-scrim enables an excellent adaptability to a wide variety of rough or roughporous surfaces such as textiles, Non Woven, Tyvek. There is a good adhesion to nonpolar surfaces such as PE and PP film.

Our tests showed that EMBLEM EASY Tape Textile is suitable for gluing most EMBLEM textiles. It can be used for gluing of several panels. Self-test are required when using the EASY Tape Textile with materials outside of the EMBLEM-range or for special demands. It is suitable for indoor and outdoor. If humidity penetrates through textiles, thereby the adhesive force is reduced. During drying process the adhesion reconstructs itself.

Due to the multiplicity of possible influences on the stuck together product no information of a minimum durability or a maximum stress can be provided.