

## EMBLEM Solvent Banner Eco II

A lightweight PVC carrier for front-lit banners. It conforms to Fire Protection Class B1 and may therefore be used both indoors and outdoors. The dull white surface is applied by calendaring, resulting in a perfectly even and dense surface, which contributes to excellent printing results.

Matchcode:	SBECO2
Material:	PVC coated scrim
Finish:	matt
Color:	white
Weight:	440 g/m <sup>2</sup>
Breaking strength:	1800 / 1300 N/5 cm
Tear strength:	180 / 165 N
Flame retardant:	acc. to DIN 4102-B1
Width of rolls:	42", 54", 63", 98"
Length of rolls:	50 m
Temperature resistance:	-30 to 70°C

### COMPATIBLE INKS:

Eco Solvent:	yes	UV:	yes
Solvent:	yes	Latex:	yes

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there are numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.

## EMBLEM Solvent Banner Eco II

### Description:

The material can be eyed, is stickable and sewable. During the finishing you have to ensure that adequate tools are used. Furthermore it is necessary that eyes are placed in a distance which is proportionated to the expected wind load and own weight of the banner.

### Application:

Main fields of application are indoor/outdoor promotional messages