

## EMBLEM Solvent Backlitfilm Lux - matt

EMBLEM Solvent Backlitfilm Lux is a translucent polyester film with bright white matt coating for backlight application indoor and outdoor. The specific surface of SOBALUX-G permits a good ink coverage as well as brilliant colours, excellent flatness and good drying time.

Matchcode:	SOBALUX-M
Material:	Polyester
Finish:	matt
Color:	translucent
Thickness:	200 µm
Dimensional stability:	at 150°C after 30 min.
lengthwise:	+1,6 %
cross direction:	+ 0,5 %
Lamination:	cool, warm
Application temperature:	more than 15° C
Flame retardant:	no
Width of rolls:	30", 36", 42", 50", 54", 60"
Length of rolls:	30 m
Durability:	under conditions of middle-european climate up to 12 month outdoor
Storage:	cool and dry environment, at 15-25°C, 50% rel. humidity
Self life:	12 month in original packing

### COMPATIBLE INKS:

Eco Solvent:	yes	UV:	yes
Solvent:	yes	Latex:	yes

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there are numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.

## EMBLEM Solvent Backlitfilm Lux - matt

### Description:

EMBLEM Solvent Backlitfilm Lux is a translucent polyester film with bright white matt coating for backlight application indoor and outdoor. The specific surface of SOBALUX-G permits a good ink coverage as well as brilliant colours, excellent flatness and good drying time. The special coating is developed for solvent, eco-solvent, UV-curable and latex inks.

### Processing:

Before further processing the VOC's of solvent, eco-solvent and latex inks must be dried completely. The drying time depends on the amount of ink. Solvent residues due to insufficient drying time can lead to blocking if stored in rolled-up form. We advice to unroll the printed strip and spread it out as soon as possible until final drying.

When the surface is subjectet to humidity, abrasion, sweat or other mechanical influences for a long time it must be protected with self-adhesive laminating films or appropriate liquid lamination products. During lamination such residues can impact the quality of the finished product (flatness, shrinkage behaviour, anchorage, adhesion power, etc) negatively.

Before printing check the correct drying temperature by carrying out a trial print. Drying temperatures which are too high can lead to a deformation of the film.

To avoid fingerprints the use of cotton-gloves is advisable.

### Application:

Illuminated displays, lightbox frames