

## EMBLEM Solvent Solvent Green Vision Film Adhesive

### EMBLEM Solvent Green Vision Film Adhesive

Matchcode:	SOGVFADH
Material:	Polyolefin film, PVC free
Finish:	glossy
Color:	white
Thickness:	85 µm
Glue:	clear solventfree acrylic glue, semi-permanent, fulfil EN71/part3 (toys regulation)
Liner:	135 g/m <sup>2</sup> , chlorine-free bleached craftliner, solventfree siliconised
Adhesion on glas: <small>(acc. FTM1)</small>	min. 8 N/25mm after 24h contact
Dimensional atability:	n. n.
Elongation at break:	n. n.
Temperature resistance:	-30°C to +90°C
Application temperature:	>+10°C
Width of rolls:	54"
Length of rolls:	50 meters
BubbleJet Dye:	no
BubbleJet Pigment:	no
Piezo Dye:	no
Piezo Pigment:	no
Piezo Oil:	no
Piezo Eco Solvent:	yes
Piezo Solvent:	yes
UV:	yes
Flame retardand:	n. n.

#### Description:

SOGVFADH is a selfadhesive, polyolefin film with a glossy surface, covered on backside with high quality coated paper.

To perform with best printquality, it is produced with a special climate stabilised liner.

With the above mentioned inks waterresistant prints are achieved.

The average durability of the film is up to 2 years by proper application.

Typical applications for SOGVFADH are short- to middle-term advertising for indoor and outdoor use like POS, displays and signs. Apply the film on plane surfaces.

We advise the use of lamination film to protect them from abrasion.

After printing it is necessary to wait for an outright drying and fumigation of the print to avoid diffusion of the solvent which could damage the glue or may cause lumps or delamination.

The subsurfaces to be paste up with the film have to be free of dust and grease. Varnishings have to be cured completely. To check compatibility between the glue and the varnish the user is advised to make tests before application.

To avoid fingerprints the use of cotton-gloves is advisable.