

## EMBLEM Solvent Ice Etch Film

### EMBLEM Solvent Ice Etch Film

Matchcode:	SOIECT
Material:	PVC polymeric
Finish:	satin
Colour:	translucent
Thickness:	80 µm
Glue:	clear glue, polyacrylic
Liner:	both side PE coated silicon paper 160 g/m <sup>2</sup>
Adhesion power- immediatly: (acc. ASTM-D-903)	ca. 2,5 N / 25 mm
Adhesion power - 1 week: (acc. ASTM-D-903)	ca. 10 N/ 25 mm
Dimensional stability:	stuck on aluminium after 48 h at 70 °C max. -0,45% (25 x 25 cm)
Application temperature:	more then 15 ° C
Service temperature:	- 30°C to + 80°C
Durability:	under conditon of middle-european cli- mate up to 7 years out- door
Flame retardant:	stuck on aluminium the film is selfextinguishing
Width of rolls:	54"
Length of rolls:	25 m
Storage:	cool and dry environ- ment, ca. 3 year
Compatible inks:	
Eco solvent:	yes
Solvent:	yes
UV-curable:	yes
Latex:	yes

### Description:

EMBLEM Solvent Ice Etch Film is a translucent glass decoration film. A satin surface and the metal pigmentation gives an exclusive noble effect. It is useful for reflection light and illuminated applications.

EMBLEM SOICET is printable with eco-solvent, solvent, UV and latex inks. The premium liner has an excellent climate stability and high thermal conductivity.

The tiny channelled Easy Bond glue is designed for dry application and repositionable without white stretch stress marks. Easy application because bubbles can easily wiped out.

To avoid fingerprints the use of cotton-gloves is advisable.

### Typical applications:

glass decoration

Because of the great number of potential influences at object time and applinace of the above-mentioned materials, on which we have no bearing, test prints have to be effected by the user himself. A legally binding warranty can not be deduced from our specifications. Every liability and warranty that goes beyond the warranty of the product amounting to the product's value as well as entitlements to damages are excluded.