

## EMBLEM Solvent Presentation Film PP

### EMBLEM Solvent Presentation Film PP

Matchcode:	SOPFPP
Material:	Polypropylen
Finish:	semiglossy
Colour:	white
Weight (ISO 536):	130 g/m <sup>2</sup>
Thickness (ISO 534):	170µ
Initial Tensile Strength:	200N / 50mm
Max. Tensil Strength:	155% (at break)
Initial Tear Strength:	1100N / 50mm
Tear Strength:	< 10N / 50mm
Storage Temperature:	10° C - 30° C
Air Humidity:	35% - 65%
Lamination:	cold
Width of roll:	36" / 54"
Length of roll:	30m
Flame retardant:	no
Eco Solvent:	yes
Solvent:	yes
Latex:	yes
UV:	yes

#### Printer compatibility (selection only):

Epson GS6000  
HP Latex series, 8000S - 10000S  
Roland Pro III-, SP-, VP-, RS- und VS-series  
Mimaki JV 5, JV3 und JV33  
Mutoh ValueJet, Osprey, Rockhopper I - III  
Seiko IP6600

#### Small print

Because of the great number of potential influences at object time and applinace of the above-mentioned materials, on which we have no bearing, test prints have to be effected by the user himself. A legally binding warranty can not be deduced from our specifications. Every liability and warranty that goes beyond the warranty of the product amounting to the product's value as well as entitlements to damages are excluded.

#### Description:

EMBLEM SOPFPP is a tear-resistant polypropylenfilm with a special coating for solvent and eco-solvent inks.

The coating allows brillant photo quality printing, short drying time and high saturation. SOPFPP is fully water-proof and most scratch resistant.

The coating makes it able to achieve high-end presentation quality with bright colours and very good contrast.

The prints are featured by minor reflections.

To avoid fingerprints it is advisable to wear cotton gloves.

#### applications:

RollUp displays, signs for in- and outdoor, POS advertisement, photoreproduction, displays